QS Safety

EXTRAFlex®

GNFN101S

15GAUGE

EN388

4131X

TOUCH SCREEN

OEKO TEX® STANDARD 100 SH020 126980 TESTEX

CE

Glove Made With 62% Recycled Content

Global Recycled Standard

GOLD | Top 5%
ecovadis
Sustainability Rating
AUG 2025

ATTRIBUTES:

- 15g Green Recycled Nylon Liner
- Black HCT® Lite Nitrile Palm Coating

APPLICATIONS:

- Handling/assembling small oily parts
- General assembly
- Machining
- Micro-engineering
- Automotive components

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

CATEGORY:

EXTRAFlex®

SUSTAINABILITY EFFORTS:

QS Safety has long been a pioneer in responsible and environmentally friendly manufacturing practices.
Over the past 30 years, we have remained committed to doing our part to produce protective gloves in the most ethical and environmentally friendly way possible.

CLEANING / MAINTENANCE:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.

qssafety.com sales@qsglove.com +86-21-62789090 Room 2701A, L' Avenue Shanghai, No. 99 Xianxia Road, Changning District, Shanghai 200051, PRC