

GNFM101S

15GAUGE

EN388

4131X

STANDARD 100
SHO20 126980
TESTEX

Global Recycled Standard


ATTRIBUTES:

- 15g Green Recycled Nylon Liner
- Black HCT® MicroFoam Nitrile Palm Coating

APPLICATIONS:

- Handling/assembling small oily parts
- General assembly
- Machining
- Micro-engineering
- Automotive components

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

SUSTAINABILITY EFFORTS:

QS Safety has long been a pioneer in responsible and environmentally friendly manufacturing practices. Over the past 30 years, we have remained committed to doing our part to produce protective gloves in the most ethical and environmentally friendly way possible.

CATEGORY:

EXTRA Flex®

CLEANING / MAINTENANCE:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.