

GHFM301S

15GAUGE



ANSI/ISEA 105



EN388



4X43D



TOUCH
SCREEN



STANDARD
100
SH020 126980
TESTEX



ATTRIBUTES:

- 15g Green Recycled Nylon And Engineered Cut D Liner
- Black HCT® NanoFoam Nitrile Palm Coating

APPLICATIONS:

- Handling/assembling small oily parts
- General assembly
- Machining
- Micro-engineering
- Automotive components

PACKAGING:

| | | | | | | |
|------------|--------|-----|--------|-------|-------|------|
| GLOVE SIZE | 6 | 7 | 8 | 9 | 10 | 11 |
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE | 6DZ | 6DZ | 6DZ | 6DZ | 6DZ | 6DZ |

SUSTAINABILITY EFFORTS:

QS Safety has long been a pioneer in responsible and environmentally friendly manufacturing practices. Over the past 30 years, we have remained committed to doing our part to produce protective gloves in the most ethical and environmentally friendly way possible.

CATEGORY:

EXTRAFlex®

CLEANING / MAINTENANCE:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.