

# NFN203R

18GAUGE



ANSI/ISEA 105



EN388



4X31B



TOUCH  
SCREEN



STANDARD  
100  
SH20 126980  
TESTEX



## ATTRIBUTES:

- 18g Green Engineered Cut B Liner
- HCT® Lite Nitrile Palm Coating

## APPLICATIONS:

- Cutting small dry or oily parts
- Automotive
- Logistics
- Gardening
- Delicate and precise operations

## PACKAGING:

|            |        |     |        |       |       |      |
|------------|--------|-----|--------|-------|-------|------|
| GLOVE SIZE | 6      | 7   | 8      | 9     | 10    | 11   |
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| PER CASE   | 6DZ    | 6DZ | 6DZ    | 6DZ   | 6DZ   | 6DZ  |

## SUSTAINABILITY EFFORTS:

QS Safety has long been a pioneer in responsible and environmentally friendly manufacturing practices. Over the past 30 years, we have remained committed to doing our part to produce protective gloves in the most ethical and environmentally friendly way possible.

## CATEGORY:

EXTRAFlex®

## CLEANING / MAINTENANCE:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.